



32-125/1.1 (1.1kW) MEI > 0.70 – impeller diameter = 133 mm




Rotation speed ≈ 2900 min⁻¹
 Test standard: ISO 9906 – Annex A

32-160/1.5 (1.5kW) MEI > 0.70 – impeller diameter = 151 mm
 32-160/2.2 (2.2kW) MEI > 0.70 – impeller diameter = 166 mm




Rotation speed ≈ 2900 min⁻¹
 Test standard: ISO 9906 – Annex A

32-200/3.0 (3.0kW) MEI > 0.40 – impeller diameter = 186 mm
 32-200/4.0 (4.0kW) MEI > 0.40 – impeller diameter = 200 mm
 32-200/7.5 (7.5kW) MEI > 0.50 – impeller diameter = 224 mm




40-125/1.5 (1.5kW) MEI > 0.50 – impeller diameter = 125 mm
 40-125/2.2 (2.2kW) MEI > 0.50 – impeller diameter = 140 mm




Rotation speed $\approx 2900 \text{ min}^{-1}$
 Test standard: ISO 9906 – Annex A

40-160/3.0 (3.0kW) MEI > 0.70 – impeller diameter = 151 mm
 40-160/4.0 (4.0kW) MEI > 0.70 – impeller diameter = 166 mm




Rotation speed $\approx 2900 \text{ min}^{-1}$
 Test standard: ISO 9906 – Annex A

40-200/5.5 (5.5kW) MEI > 0.70 – impeller diameter = 183 mm
 40-200/7.5 (7.5kW) MEI > 0.70 – impeller diameter = 200 mm
 40-200/11 (11kW) MEI > 0.70 – impeller diameter = 224 mm




Rotation speed ≈ 2900 min⁻¹
 Test standard: ISO 9906 – Annex A

50-125/2.2 (2.2kW) MEI > 0.60 – impeller diameter = 126 mm
 50-125/3.0 (3.0kW) MEI > 0.60 – impeller diameter = 131 mm
 50-125/4.0 (4.0kW) MEI > 0.60 – impeller diameter = 140 mm




Rotation speed ≈ 2900 min⁻¹
 Test standard: ISO 9906 – Annex A

50-160/5.5 (5.5kW) MEI > 0.70 – impeller diameter = 154 mm
 50-160/7.5 (7.5kW) MEI > 0.70 – impeller diameter = 166 mm




Rotation speed ≈ 2900 min⁻¹
 Test standard: ISO 9906 – Annex A

50-200/9.2 (9.2kW) MEI > 0.70 – impeller diameter = 191 mm
 50-200/11 (11kW) MEI > 0.70 – impeller diameter = 200 mm
 50-200/15 (15kW) MEI > 0.70 – impeller diameter = 224 mm




Rotation speed $\approx 2900 \text{ min}^{-1}$
 Test standard: ISO 9906 – Annex A

65-125/4.0 (4.0kW) MEI > 0.70 – impeller diameter = 128 mm
 65-125/5.5 (5.5kW) MEI > 0.70 – impeller diameter = 138 mm
 65-125/7.5 (7.5kW) MEI > 0.70 – impeller diameter = 149 mm




Rotation speed $\approx 2900 \text{ min}^{-1}$
 Test standard: ISO 9906 – Annex A

65-160/7.5 (7.5kW) MEI > 0.70 – impeller diameter = 153 mm
 65-160/9.2 (9.2kW) MEI > 0.70 – impeller diameter = 161 mm
 65-160/11 (11kW) MEI > 0.70 – impeller diameter = 168 mm
 65-160/15 (15kW) MEI > 0.70 – impeller diameter = 178 mm



Rotation speed ≈ 2900 min⁻¹
 Test standard: ISO 9906 – Annex A

65-200/15 (15kW) MEI > 0.60 – impeller diameter = 190 mm
 65-200/18.5 (18.5kW) MEI > 0.60 – impeller diameter = 201 mm
 65-200/22 (22kW) MEI > 0.60 – impeller diameter = 212 mm



Rotation speed $\approx 2900 \text{ min}^{-1}$
 Test standard: ISO 9906 – Annex A