

## AMORTIGUADORES ANTIVIBRATORIOS SILENTBLOCK\*\*TOPES DE GOMA\*\*R

	REF / ART.NR		DIMENSIONES				COMPRESIÓN	
		Sh	ØA	B	D	C	CARGA	FLECHA
			mm.				kg.	mm.
R	R1215	60	12	15	M-05	10	15	3,0±0,5
	R1610	60	16	10	M-05	12	20	1,5±0,5
	R1615	60	16	15	M-05	12	15	2,5±0,5
	R1620	60	16	20	M-05	12	15	3,5±0,5
	R1625	60	16	25	M-05	12	15	4,5±1,0
	R2008	60	20	8	M-06	15	45	1,6±0,5
	R2015	60	20	15	M-06	15	35	3,0±0,5
	R2020	60	20	20	M-06	15	25	4,0±1,0
	R2025	60	20	25	M-06	15	25	5,0±1,0
	R2030	60	20	30	M-06	15	25	6,0±1,0
	R2510	50	25	10	M-08	20	50	2,0±0,5
	R2515	50	25	15	M-08	20	40	3,0±0,5
	R2520	50	25	20	M-08	20	40	4,0±0,5
	R2525	50	25	25	M-08	20	40	5,0±1,0
	R2530	50	25	30	M-08	20	40	6,0±1,0
	R2540	50	25	40	M-08	20	40	8,0±1,0
	R2822	50	28	22	M-08	20	60	5,0±1,0
	R3010	50	30	10	M-08	20	80	2,0±0,5
	R3015	50	30	15	M-08	20	80	3,0±0,5
	R3020	50	30	20	M-08	20	80	4,0±0,5
	R3030	50	30	30	M-08	20	60	6,0±1,0
	R3040	50	30	40	M-08	20	60	8,0±1,0
	R4020M8X20	50	40	20	M-08	20	140	4,0±0,5
	R4020	50	40	20	M-10	25	140	4,0±0,5
	R4028M8X20	50	40	28	M-08	20	100	5,5±1,0
	R4028	50	40	28	M-10	25	100	5,5±1,0
	R4035	50	40	35	M-10	25	100	7,0±1,0
	R4040M8X20	50	40	40	M-08	20	100	8,0±1,0
	R4040	50	40	40	M-10	25	100	8,0±1,0
	R4045	50	40	45	M-10	25	90	9,0±1,0
	R5020	50	50	20	M-10	25	300	4,0±0,5
	R5025	50	50	25	M-10	25	175	5,0±1,0
	R5030	50	50	30	M-10	25	160	6,0±1,0
	R 5035	50	50	35	M-10	25	160	7,0±1,0
	R5040	50	50	40	M-10	25	155	8,0±1,0
	R5045	50	50	45	M-10	25	150	9,0±1,0
	R5060	50	50	60	M-10	25	130	12,0±1,5
	R6025	50	60	25	M-10	25	400	5,0±1,0
	R6035	50	60	35	M-10	25	300	7,0±1,0
	R6045	50	60	45	M-10	25	250	9,0±1,0
	R6060	50	60	60	M-10	25	225	12,0±1,5
	R7035M10X25	50	70	35	M-10	25	450	7,0±1,0
	R7040M10X25	50	70	40	M-10	25	400	8,0±1,0
	R7050M10X25	50	70	50	M-10	25	300	10,0±1,0
	R 070M10X25	50	70	70	M-10	25	300	14,0±1,5
	R7035	50	70	35	M-12	33	450	7,0±1,0
	R7040	50	70	40	M-12	33	400	8,0±1,0
	R7050	50	70	50	M-12	33	300	10,0±1,0
	R7070	50	70	70	M-12	33	300	14,0±1,5
	R7525	50	75	25	M-12	33	650	5,0±1,0
	R8030	50	80	30	M-14	35	950	6,0±1,0
	R8040	50	80	40	M-14	35	600	8,0±1,0
	R8055	50	80	55	M-14	35	500	11,0±1,5
	R9525	60	95	25	M-16	42	1800	5,0±1,0
	R9540	50	95	40	M-16	42	1000	8,0±1,0

